

Material:	Polyethylene
Shrink Ratio:	3:1
Adhesive Adheres to:	Most plastics, metals, rubber,
Continuous Operating Temperature:	-45C up to +145C
Longitudinal Shrinkage (Lengthwise):	Less than 8%
Insulating Voltage Capability:	600 volts
Warranty:	1 Year
Resistant to:	Salt water, Oil, Gasoline, Diesel Fuel, and more
Applications:	Marine, Automotive / Motorsports, Industrial, Environmental sealing. For use as a strain relief on connectors, wire and terminals. Splicing, abrasion protection, and repair of damaged wire insulation.

Nominal Size (inch)	Recommended Best Fit Wire Range	Supplied ID		Contracted ID		Total Contracted Wall Thickness (Nominal)		Adhesive Contracted Wall Thickness	
		Inch	mm	Inch	mm	Inch	mm	Inch	mm
		1/8"	< 14 AWG	0.13	3.2	0.04	1	0.04	1
3/16"	22 - 12 AWG	0.19	4.8	0.06	1.6	0.04	1.1	0.02	0.4
1/4"	18 - 10 AWG	0.25	6.4	0.08	2	0.05	1.2	0.02	0.5
5/16"	14 - 8 AWG	0.31	7.9	0.11	2.7	0.06	1.4	0.02	0.5
3/8"	12 - 6 AWG	0.37	9.5	0.13	3.2	0.06	1.4	0.02	0.5
1/2"	8 - 4 AWG	0.50	12.7	0.17	4.2	0.07	1.7	0.02	0.5
9/16"	6 - 1 AWG	0.59	15	0.20	5.2	0.07	1.8	0.02	0.6
3/4"	4 - 2/0 AWG	0.75	19.1	0.25	6.3	0.08	2	0.02	0.6
1"		1.00	25.4	0.33	8.5	0.08	2.1	0.02	0.6
1 3/16" (1.25")		1.18	30	0.40	10.2	0.09	2.2	0.02	0.6
1.5"		1.54	39	0.53	13.5	0.09	2.4	0.02	0.6
2"		1.97	50	0.67	17	0.11	2.7	0.03	0.7